FM 15-270

SPECIFICATIONS

Make		FUSO
Range		Fighter
Model		FM15-270 TIP
Model Code		FM65FF2DRBJ1
Axle Layout		4X2
Cab		Forward Control
Crew		3 seating
Vehicle type		Tipper
Mass Data (kg)	
GVM	Manufacturer's gross vehicle mass	15100
GCM	Manufacturer's gross combination mass	32000
D/T	Permissible max towing drawing vehicle mass	32000
GA-Front	Manufacturer's front axle mass	6000
GA-Rear	Manufacturer's rear axle mass	9700
V	Permissible maximum vehicle mass	15000
AF	Permissible maximum front axle mass	6000
AR	Permissible maximum rear axle mass	9000
UF	Unladen front axle mass	2825
UR	Unladen rear axle mass	1920
UT (Tare)	Total unladen mass	4745
Permissible Body		10355
Fuel Tank (Litres)	Capacity	200
Dimensions (m		
OL	Overall length	6690
OW	Overall width	2470
CA	Cab to Axle	2935
OH	Overall height	2690
FOH	Front overhang	1245
ROH	Rear overhang	1700
WB	Wheelbase	3680
Performance		
Gradeability at Permissible Maximum Weight (V)		58%
Maximum Speed (SA Legislation)		80 km/h
Minimum turning radius		7.1 m
Standard Equi	pment/features	
	System (ABS) Exhaust Brake System	
Lockable Fuel Tar	'	
Outside mirror with long stay Seatbelt for driver, front centre and driver assistant		
Ashtray on door for driver and assistant		
Cigarette lighter		
Sunvisor for Drive	r and assistant	
Interior mirror		
Heater and defros	ter	
Dual type electric		
All lamps with E.e		
Intelligent Instrument cluster		
Telescopic and tilt steering column with Steering lock		

Engine	
Make	FUSO
Model	6M60-1AT2
Configuration	Diesel inline 6
Capacity (cm3)	7545
Туре	"Four stroke water cooled direct injection diesel engine, Turbo charged"
Power at RPM	199 @ 2600 - 2600
Torque at RPM	786 @ 1400 - 1400
Emission standards	Euro 2
Generator	24 V / 50 A
Air Cleaner	Dry paper element type
Suction	Snorkel and rain cap
Governor	Electrical control type
Transmission	
Make	EATON
Model	FS-8209
Туре	Synchromesh gears
Shift	Manual
No. of gears forward	9
First gear ratio	12.6
Top gear ratio	1
Clutch	
Make	FUSO
Model	C7M38
Туре	Hydraulic
Diameter (mm)	380
Drive Axle	
	D052H
Model Reduction type	Single
Final Ratio	4,625
	4.023
Suspension	
Front	Long taper leaf springs with double acting type shock absorbers
Rear	Laminated leaf springs
Steering	
	Hydraulic power assisted
Brakes	
System type	Full Air, Dual circuit, Wedge type
Front	Drum
Rear	Drum
ABS	Yes
Park/Emergency System	Yes
Auxiliary Brakes	Exhaust brake
Tyres and Rims	
Tyre Sizes	11R22.5
Wheel type	Drum Type
Electrical	
System	24V

Details not binding - subject to change without notice 03/2021



Filter minder
Reverse Warning Buzzer"

Standard Services

4 Years / 300 000 km warranty

20 000km maintenance schedule

DIMENSIONS







